

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
AlA: Altvan-----	90	Poor Too sandy Low content of organic matter Droughty Water erosion	0.00 0.12 0.93 0.99	Good		Poor Too sandy Rock fragments Hard to reclaim	0.00 0.00 0.92
AlB: Altvan-----	95	Poor Too sandy Low content of organic matter Droughty Water erosion	0.00 0.12 0.93 0.99	Good		Poor Too sandy Rock fragments Hard to reclaim	0.00 0.00 0.92
AnB: Anselmo-----	70	Fair Too sandy Low content of organic matter	0.03 0.12	Good		Fair Too sandy	0.03
AnC: Anselmo-----	85	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
ApC: Anselmo-----	70	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
Duda-----	20	Poor Wind erosion Droughty Too sandy Low content of organic matter Depth to bedrock	0.00 0.00 0.00 0.50 0.58	Poor Depth to bedrock	0.00	Poor Too sandy Depth to bedrock	0.00 0.58

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
ArC: Anselmo-----	45	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
Ronson-----	30	Fair Droughty Depth to bedrock Low content of organic matter	0.19 0.58 0.88	Poor Depth to bedrock	0.00	Fair Depth to bedrock	0.58
AtE: Anselmo-----	46	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy Slope	0.02 0.16
Longpine-----	30	Poor Droughty Depth to bedrock Low content of organic matter	0.00 0.00 0.88	Poor Depth to bedrock	0.00	Poor Depth to bedrock Rock fragments Slope	0.00 0.00 0.00
AuE: Anselmo-----	35	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy Slope	0.02 0.37
Tuthill-----	30	Good		Good		Fair Slope	0.37
AvA: Anselmo-----	55	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
Vetal-----	30	Good		Good		Good	

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
AvB: Anselmo-----	60	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
Vetal-----	30	Good		Good		Good	
BsD: Boyd-----	70	Poor Too clayey Droughty Depth to bedrock Water erosion	0.00 0.01 0.58 0.99	Poor Depth to bedrock Shrink-swell Low strength	0.00 0.00 0.00	Poor Too Clayey Depth to bedrock	0.00 0.58
Sansarc-----	25	Poor Too clayey Droughty Depth to bedrock Low content of organic matter Water erosion	0.00 0.00 0.00 0.60 0.99	Poor Depth to bedrock Shrink-swell Low strength	0.00 0.00 0.00	Poor Too Clayey Depth to bedrock Slope	0.00 0.00 0.16
CaA: Chappell-----	60	Fair Low content of organic matter Droughty	0.12 0.54	Good		Poor Hard to reclaim	0.00
Anselmo-----	30	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
CaB: Chappell-----	55	Fair Low content of organic matter Droughty	0.12 0.54	Good		Poor Hard to reclaim	0.00

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Anselmo-----	25	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
DcC: Dix-----	50	Poor Too sandy Low content of organic matter Droughty	0.00 0.12 0.23	Good		Poor Hard to reclaim Too sandy Rock fragments Hard to reclaim	0.00 0.00 0.00 0.02
Chappell-----	30	Fair Low content of organic matter Droughty	0.12 0.54	Good		Poor Hard to reclaim	0.00
DfA: Doger-----	80	Poor Wind erosion Too sandy Droughty	0.00 0.45 0.95	Good		Fair Too sandy	0.45
DgB: Doger-----	65	Poor Wind erosion Too sandy Droughty	0.00 0.45 0.95	Good		Fair Too sandy	0.45
Dunday-----	20	Poor Wind erosion Low content of organic matter Too sandy Droughty	0.00 0.12 0.51 0.95	Good		Fair Too sandy	0.51

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
D1B: Duda-----	70	Poor Wind erosion Droughty Low content of organic matter Too sandy Depth to bedrock	0.00 0.00 0.50 0.51 0.58	Poor Depth to bedrock	0.00	Fair Too sandy Depth to bedrock	0.51 0.58
DsA: Dunday-----	90	Poor Wind erosion Low content of organic matter Too sandy Droughty	0.00 0.12 0.51 0.95	Good		Fair Too sandy	0.51
DuA: Dunday-----	90	Poor Wind erosion Low content of organic matter Too sandy Droughty	0.00 0.12 0.51 0.95	Good		Fair Too sandy	0.51
ElA: Elsmere-----	65	Poor Wind erosion Low content of organic matter Too sandy	0.00 0.12 0.28	Fair Depth to saturated zone	0.76	Fair Too sandy Depth to saturated zone	0.28 0.76
EpF: Epping-----	65	Poor Depth to bedrock Droughty Low content of organic matter Water erosion	0.00 0.00 0.88 0.90	Poor Depth to bedrock Slope Low strength	0.00 0.00 0.22	Poor Slope Depth to bedrock	0.00 0.00

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Keota-----	20	Fair Low content of organic matter Depth to bedrock Droughty Water erosion	0.12 0.58 0.64 0.90	Poor Depth to bedrock Slope	0.00 0.00	Poor Slope Depth to bedrock	0.00 0.58
Ge: Gannett-----	70	Fair Low content of organic matter Droughty	0.12 0.99	Poor Depth to saturated zone	0.00	Poor Depth to saturated zone	0.00
Gh: Goshen-----	90	Fair Low content of organic matter Water erosion	0.12 0.90	Fair Low strength Shrink-swell	0.78 0.99	Good	
Gr: Schamber-----	45	Poor Too sandy Droughty Low content of organic matter	0.00 0.00 0.50	Fair Slope	0.92	Poor Too sandy Hard to reclaim Rock fragments Slope	0.00 0.00 0.00 0.00
Dix-----	40	Poor Too sandy Low content of organic matter Droughty	0.00 0.12 0.23	Good		Poor Hard to reclaim Too sandy Rock fragments Hard to reclaim Slope	0.00 0.00 0.00 0.02 0.37
HfA: Holt-----	85	Poor Droughty Depth to bedrock Sodium content	0.00 0.58 0.97	Not Rated Depth to bedrock	0.00	Fair Depth to bedrock	0.58

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
H1C: Holt-----	40	Poor Droughty Depth to bedrock Sodium content	0.00 0.58 0.97	Not Rated Depth to bedrock	0.00	Fair Depth to bedrock	0.58
Vet1-----	20	Good		Good		Good	
HmA: Hoven-----	90	Poor Too clayey Sodium content Low content of organic matter Salinity Water erosion	0.00 0.00 0.50 0.88 0.99	Poor Depth to saturated zone Shrink-swell Low strength	0.00 0.00 0.00	Poor Depth to saturated zone Too Clayey Sodium content Salinity	0.00 0.00 0.00 0.00
HnA: Jerauld-----	80	Poor Sodium content Low content of organic matter Too clayey Salinity Water erosion	0.00 0.12 0.32 0.88 0.99	Poor Low strength Shrink-swell	0.00 0.00	Poor Sodium content Salinity Too Clayey	0.00 0.00 0.19
HuA: Huggins-----	85	Poor Too clayey Depth to bedrock Droughty	0.00 0.16 0.39	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.30	Poor Too Clayey Depth to bedrock	0.00 0.16
HwB: Huggins-----	55	Poor Too clayey Depth to bedrock Droughty	0.00 0.16 0.39	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.30	Poor Too Clayey Depth to bedrock	0.00 0.16
Kadoka-----	30	Fair Depth to bedrock Water erosion	0.58 0.90	Poor Depth to bedrock Low strength	0.00 0.00	Fair Depth to bedrock	0.58

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
In: Inavale-----	90	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Good		Poor Too sandy	0.00
Iw: Inavale-----	75	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Good		Poor Too sandy	0.00
Bigwinder-----	20	Fair Low content of organic matter	0.88	Fair Depth to saturated zone	0.53	Fair Depth to saturated zone	0.53
KaA: Kadoka-----	85	Fair Depth to bedrock Water erosion	0.58 0.90	Poor Depth to bedrock Low strength	0.00 0.00	Fair Depth to bedrock	0.58
KbC: Kadoka-----	55	Fair Depth to bedrock Water erosion	0.58 0.90	Poor Depth to bedrock Low strength	0.00 0.00	Fair Depth to bedrock	0.58
Epping-----	15	Poor Depth to bedrock Droughty Low content of organic matter Water erosion	0.00 0.00 0.88 0.90	Poor Depth to bedrock Low strength	0.00 0.22	Poor Depth to bedrock	0.00
KdB: Kadoka-----	50	Fair Depth to bedrock Water erosion	0.58 0.90	Poor Depth to bedrock Low strength	0.00 0.00	Fair Depth to bedrock	0.58
Huggins-----	37	Poor Too clayey Depth to bedrock Droughty	0.00 0.16 0.39	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.30	Poor Too Clayey Depth to bedrock	0.00 0.16

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
KdC: Kadoka-----	65	Fair Depth to bedrock Water erosion	0.58 0.90	Poor Depth to bedrock Low strength	0.00 0.00	Fair Depth to bedrock	0.58
Huggins-----	25	Poor Too clayey Depth to bedrock Droughty	0.00 0.16 0.39	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.30	Poor Too Clayey Depth to bedrock	0.00 0.16
KeA: Keith-----	90	Fair Low content of organic matter Water erosion	0.12 0.90	Good		Good	
KeC: Keith-----	60	Fair Low content of organic matter Water erosion	0.12 0.90	Good		Good	
KgD: Keith-----	45	Fair Low content of organic matter Water erosion	0.12 0.90	Good		Fair Slope	0.84
Epping-----	30	Poor Depth to bedrock Droughty Low content of organic matter Water erosion	0.00 0.00 0.88 0.90	Poor Depth to bedrock Low strength	0.00 0.22	Poor Depth to bedrock Slope	0.00 0.37
KhE: Keota-----	40	Fair Low content of organic matter Depth to bedrock Droughty Water erosion	0.12 0.58 0.64 0.90	Poor Depth to bedrock	0.00	Poor Slope Depth to bedrock	0.00 0.58

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Epping-----	35	Poor Depth to bedrock Droughty Low content of organic matter Water erosion	0.00 0.00 0.88 0.90	Poor Depth to bedrock Low strength	0.00 0.22	Poor Depth to bedrock Slope	0.00 0.37
KkD: Keota-----	45	Fair Low content of organic matter Depth to bedrock Droughty Water erosion	0.12 0.58 0.64 0.90	Poor Depth to bedrock	0.00	Fair Slope Depth to bedrock	0.37 0.58
Kadoka-----	40	Fair Depth to bedrock Water erosion	0.58 0.90	Poor Depth to bedrock Low strength	0.00 0.00	Fair Slope Depth to bedrock	0.37 0.58
KrF: Keota-----	35	Fair Low content of organic matter Depth to bedrock Droughty Water erosion	0.12 0.58 0.64 0.90	Poor Depth to bedrock Slope	0.00 0.00	Poor Slope Depth to bedrock	0.00 0.58
Epping-----	30	Poor Depth to bedrock Droughty Low content of organic matter Water erosion	0.00 0.00 0.88 0.90	Poor Depth to bedrock Slope Low strength	0.00 0.00 0.22	Poor Slope Depth to bedrock	0.00 0.00
Rock Outcrop, Soft--	20	Not rated		Not rated		Not rated	
Ky: Keya-----	85	Fair Low content of organic matter	0.12	Good		Good	

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
La: Fluvents, Loamy-----	99	Not rated		Not rated		Not rated	
Le: Loup-----	60	Poor Too sandy	0.00	Poor Depth to saturated zone	0.00	Poor Too sandy	0.00
		Low content of organic matter	0.88			Depth to saturated zone	0.00
		Droughty	0.91				
Elsmere-----	25	Poor Wind erosion	0.00	Fair Depth to saturated zone	0.76	Fair Too sandy	0.28
		Low content of organic matter	0.12			Depth to saturated zone	0.76
		Too sandy	0.28				
MaD: Mckelvie-----	90	Poor Too sandy	0.00	Fair Slope	0.98	Poor Too sandy	0.00
		Wind erosion	0.00			Slope	0.00
		Low content of organic matter	0.12				
MaF: Mckelvie-----	70	Poor Too sandy	0.00	Poor Slope	0.00	Poor Slope	0.00
		Wind erosion	0.00			Too sandy	0.00
		Low content of organic matter	0.12				
Peji-----	20	Poor Too sandy	0.00	Poor Depth to bedrock	0.00	Poor Slope	0.00
		Wind erosion	0.00	Slope	0.00	Too sandy	0.00
		Droughty	0.00			Depth to bedrock	0.58
		Low content of organic matter	0.12				
		Depth to bedrock	0.58				

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
MaG: Mckelvie-----	70	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Poor Slope	0.00	Poor Slope Too sandy	0.00 0.00
Peji-----	20	Poor Too sandy Wind erosion Droughty Low content of organic matter Depth to bedrock	0.00 0.00 0.00 0.12 0.58	Poor Depth to bedrock Slope	0.00 0.00	Poor Slope Too sandy Depth to bedrock	0.00 0.00 0.58
MaHG: Mckelvie-----	55	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Poor Slope	0.00	Poor Slope Too sandy	0.00 0.00
Blula-----	20	Fair Too sandy Low content of organic matter	0.41 0.50	Poor Slope	0.00	Poor Slope Too sandy	0.00 0.41
Peji-----	20	Poor Too sandy Wind erosion Droughty Low content of organic matter Depth to bedrock	0.00 0.00 0.00 0.12 0.58	Poor Depth to bedrock Slope	0.00 0.00	Poor Slope Too sandy Depth to bedrock	0.00 0.00 0.58
MbA: Millboro-----	90	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.99	Poor Shrink-swell Low strength	0.00 0.00	Poor Too Clayey	0.00

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
MbB: Millboro-----	95	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.99	Poor Shrink-swell Low strength	0.00 0.00	Poor Too Clayey	0.00
MbC: Millboro-----	90	Poor Too clayey Low content of organic matter Water erosion	0.00 0.12 0.99	Poor Shrink-swell Low strength	0.00 0.00	Poor Too Clayey	0.00
MhA: Mosher-----	80	Poor Sodium content Low content of organic matter Salinity Water erosion	0.00 0.12 0.88 0.99	Fair Shrink-swell	0.40	Poor Salinity Rock fragments Sodium content Hard to reclaim	0.00 0.03 0.90 0.98
MmA: Mosher-----	69	Poor Sodium content Low content of organic matter Salinity Water erosion	0.00 0.12 0.88 0.99	Fair Shrink-swell	0.40	Poor Salinity Rock fragments Sodium content Hard to reclaim	0.00 0.03 0.90 0.98
Minatare-----	30	Poor Too alkaline Sodium content Salinity Low content of organic matter Carbonate content Water erosion	0.00 0.00 0.00 0.12 0.97 0.99	Fair Depth to saturated zone	0.53	Poor Sodium content Salinity Depth to saturated zone Carbonate content	0.00 0.00 0.53 0.97

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
OkC: Okreek-----	90	Poor Too clayey Droughty Depth to bedrock Water erosion	0.00 0.73 0.90 0.99	Poor Depth to bedrock Shrink-swell Low strength	0.00 0.00 0.00	Poor Too Clayey Depth to bedrock	0.00 0.90
OoE: Okreek-----	60	Poor Too clayey Droughty Depth to bedrock Water erosion	0.00 0.73 0.90 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.00	Poor Too Clayey Slope Depth to bedrock	0.00 0.63 0.90
Orella-----	30	Poor Droughty Depth to bedrock Too clayey Sodium content Salinity Low content of organic matter Water erosion	0.00 0.00 0.00 0.00 0.88 0.88 0.99	Not Rated Depth to bedrock	0.00	Poor Depth to bedrock Too Clayey Sodium content Salinity Slope	0.00 0.00 0.00 0.00 0.04
OrF: Orella-----	40	Poor Droughty Depth to bedrock Too clayey Sodium content Salinity Low content of organic matter Water erosion	0.00 0.00 0.00 0.00 0.88 0.88 0.99	Not Rated Depth to bedrock Slope	0.00 0.08	Poor Slope Depth to bedrock Too Clayey Sodium content Salinity	0.00 0.00 0.00 0.00 0.00
Rock Outcrop, Soft--	25	Not rated		Not rated		Not rated	
Pm: Cutcomb-----	80	Good		Not Rated Depth to saturated zone	0.00	Poor Depth to saturated zone Content of organic matter	0.00 0.01

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
RcE: Rosebud-----	23	Fair Depth to bedrock Low content of organic matter Droughty Water erosion	0.58 0.88 0.93 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.98	Fair Slope Depth to bedrock	0.37 0.58
Canyon-----	22	Poor Droughty Depth to bedrock Low content of organic matter	0.00 0.00 0.88	Poor Depth to bedrock	0.00	Poor Depth to bedrock Slope Rock fragments	0.00 0.00 0.88
RdA: Richfield-----	77	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength Shrink-swell	0.00 0.69	Good	
Dawes-----	20	Poor Too alkaline Sodium content Low content of organic matter Water erosion	0.00 0.10 0.12 0.90	Fair Shrink-swell	0.98	Fair Sodium content Hard to reclaim	0.10 0.98
RhB: Richfield-----	45	Fair Low content of organic matter Water erosion	0.12 0.90	Poor Low strength Shrink-swell	0.00 0.69	Good	
Tuthill-----	40	Good		Good		Good	
RnA: Ronson-----	55	Fair Droughty Depth to bedrock Low content of organic matter	0.19 0.58 0.88	Poor Depth to bedrock	0.00	Fair Depth to bedrock	0.58

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Anselmo-----	25	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
RnB: Ronson-----	50	Fair Droughty Depth to bedrock Low content of organic matter	0.19 0.58 0.88	Poor Depth to bedrock	0.00	Fair Depth to bedrock	0.58
Anselmo-----	30	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02
Ru: Peji-----	40	Poor Too sandy Wind erosion Droughty Low content of organic matter Depth to bedrock	0.00 0.00 0.00 0.12 0.58	Poor Depth to bedrock Slope	0.00 0.00	Poor Slope Too sandy Depth to bedrock	0.00 0.00 0.58
Mckelvie-----	35	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Fair Slope	0.08	Poor Too sandy Slope	0.00 0.00
Sa: Els-----	50	Poor Too sandy Wind erosion Low content of organic matter Droughty	0.00 0.00 0.12 0.99	Fair Depth to saturated zone	0.76	Poor Too sandy Depth to saturated zone	0.00 0.76

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Selia-----	40	Poor Too sandy Wind erosion Sodium content Too alkaline Low content of organic matter	0.00 0.00 0.00 0.00 0.12	Fair Depth to saturated zone	0.53	Poor Too sandy Sodium content Depth to saturated zone	0.00 0.22 0.53
SbE: Sansarc-----	55	Poor Too clayey Droughty Depth to bedrock Low content of organic matter Water erosion	0.00 0.00 0.00 0.60 0.99	Poor Depth to bedrock Slope Shrink-swell Low strength	0.00 0.00 0.00 0.00	Poor Slope Too Clayey Depth to bedrock	0.00 0.00 0.00
Boyd-----	40	Poor Too clayey Droughty Depth to bedrock Water erosion	0.00 0.01 0.58 0.99	Poor Depth to bedrock Shrink-swell Low strength Slope	0.00 0.00 0.00 0.00	Poor Slope Too Clayey Depth to bedrock	0.00 0.00 0.58
Sd: Yockey-----	50	Fair Low content of organic matter Water erosion Sodium content	0.12 0.90 0.97	Fair Depth to saturated zone	0.76	Fair Depth to saturated zone Sodium content	0.76 0.98
Bigwinder-----	40	Fair Low content of organic matter	0.88	Fair Depth to saturated zone	0.53	Fair Depth to saturated zone	0.53
SnC: Shena-----	60	Poor Droughty Depth to bedrock Too clayey	0.00 0.00 0.00	Not Rated Depth to bedrock	0.00	Poor Depth to bedrock Too Clayey	0.00 0.00

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
TcF: Longpine-----	40	Poor Droughty Depth to bedrock Low content of organic matter	0.00 0.00 0.88	Poor Depth to bedrock Slope	0.00 0.00	Poor Slope Depth to bedrock Rock fragments	0.00 0.00 0.00
Rock Outcrop, Soft--	20	Not rated		Not rated		Not rated	
TfE: Longpine-----	50	Poor Droughty Depth to bedrock Low content of organic matter	0.00 0.00 0.88	Poor Depth to bedrock Slope	0.00 0.92	Poor Depth to bedrock Rock fragments Slope	0.00 0.00 0.00
Ronson-----	25	Fair Droughty Depth to bedrock Low content of organic matter	0.19 0.58 0.88	Poor Depth to bedrock Slope	0.00 0.92	Poor Slope Depth to bedrock	0.00 0.00 0.58
ThA: Tuthill-----	90	Good		Good		Good	
ThB: Tuthill-----	75	Good		Good		Good	
ThC: Tuthill-----	80	Good		Good		Good	
TnC: Tuthill-----	50	Good		Good		Good	
Anselmo-----	25	Fair Too sandy Low content of organic matter	0.02 0.12	Good		Fair Too sandy	0.02

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
TtC: Tuthill-----	35	Good		Good		Good	
Longpine-----	30	Poor Droughty Depth to bedrock Low content of organic matter	0.00 0.00 0.88	Poor Depth to bedrock	0.00	Poor Depth to bedrock Rock fragments	0.00 0.00
TvA: Tuthill-----	50	Good		Good		Good	
Vetal-----	28	Good		Good		Good	
TwA: Tuthill-----	45	Good		Good		Good	
Wortman-----	25	Poor Sodium content Droughty Depth to bedrock Salinity Water erosion	0.00 0.35 0.58 0.88 0.99	Poor Depth to bedrock Low strength	0.00 0.22	Poor Sodium content Salinity Depth to bedrock	0.00 0.00 0.58
VaE: Valentine-----	99	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Fair Slope	0.82	Poor Too sandy Slope	0.00 0.00
VdC: Valentine-----	55	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Good		Poor Too sandy	0.00

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Dunday-----	35	Poor Wind erosion Low content of organic matter Too sandy Droughty	0.00 0.12 0.51 0.95	Good		Fair Too sandy	0.51
VsE: Valentine-----	55	Poor Too sandy Wind erosion Low content of organic matter	0.00 0.00 0.12	Fair Slope	0.82	Poor Too sandy Slope	0.00 0.00
Tassel-----	25	Poor Droughty Depth to bedrock	0.00 0.00	Not Rated Depth to bedrock Slope	0.00 0.00	Poor Slope Depth to bedrock	0.00 0.00
Vt: Vetal-----	85	Good		Good		Good	
w: Water (less Than 40 Acres)-----	100	Not rated		Not rated		Not rated	
WbA: Wanblee-----	45	Fair Droughty Depth to bedrock Salinity Sodium content Water erosion	0.04 0.58 0.88 0.90 0.99	Poor Depth to bedrock Low strength	0.00 0.00	Poor Salinity Depth to bedrock Sodium content	0.00 0.58 0.90
Wortman-----	35	Poor Sodium content Depth to bedrock Droughty Salinity Water erosion	0.00 0.58 0.60 0.88 0.99	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.22 0.72	Poor Sodium content Salinity Depth to bedrock	0.00 0.00 0.58

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Wd: Wann-----	85	Fair Low content of organic matter Sodium content	0.88 0.97	Fair Depth to saturated zone	0.91	Fair Depth to saturated zone Rock fragments Sodium content	0.91 0.97 0.98
We: Wann-----	70	Fair Low content of organic matter Sodium content	0.88 0.97	Fair Depth to saturated zone	0.91	Fair Depth to saturated zone Rock fragments Sodium content	0.91 0.97 0.98
WhA: Whitelake-----	85	Poor Sodium content Low content of organic matter Salinity	0.00 0.12 0.88	Good		Poor Sodium content Salinity	0.00 0.00
WoA: Wortman-----	50	Poor Wind erosion Too clayey Sodium content Droughty Low content of organic matter Depth to bedrock	0.00 0.00 0.00 0.38 0.50 0.58	Poor Depth to bedrock Low strength Shrink-swell	0.00 0.00 0.12	Poor Sodium content Too Clayey Depth to bedrock	0.00 0.00 0.58
WrA: Wortman-----	70	Poor Sodium content Depth to bedrock Droughty Salinity Water erosion	0.00 0.58 0.60 0.88 0.99	Poor Depth to bedrock Low strength	0.00 0.22	Poor Sodium content Salinity Depth to bedrock	0.00 0.00 0.58

Section II
Soil and Site Information

Construction Materials Table 2
Todd County, South Dakota

(The information in this table indicates the dominant soil condition but does not eliminate the need for onsite investigation. The ratings given for the thickest layer are for the thickest layer above and excluding the bottom layer. The numbers in the value columns range from 0.00 to 0.99. The greater the value, the greater the likelihood that the bottom layer or thickest layer of the soil is a source of sand or gravel. See text for further explanation of ratings in this table.)

Map symbol and soil name	Pct. of map unit	Potential source of reclamation material		Potential source of roadfill		Potential source of topsoil	
		Rating class and limiting features	Value	Rating class and limiting features	Value	Rating class and limiting features	Value
Yb: Yockey-----	60	Fair Low content of organic matter Water erosion Sodium content	0.12 0.90 0.97	Fair Depth to saturated zone	0.76	Fair Depth to saturated zone Sodium content	0.76 0.98
Bigwinder-----	35	Fair Low content of organic matter	0.88	Fair Depth to saturated zone	0.53	Fair Depth to saturated zone	0.53

